# SAFETY DATA SHEET

**Product:** 597-A Revision Date: 6/01/2015

### 1. MATERIAL IDENTIFICATION

Product Name: Pyro-Duct 597-A

Product Description: Silver, Odorless Paste

Product Use: High Temperature, Silver-Filled, Electrically Conductive Adhesive

**Manufacturer:** Aremoo Products, Inc. 707-B Executive Blvd.

Valley Cottage, NY 10989

**Telephone**: 845-268-0039

**Emergency Phone:** 845-268-0039 or Infotrac (24/7) 800-535-5053

## 2. HAZARDS IDENTIFICATION

GHS Classification:

Eye Irritation Category 2A Skin Irritation Category 2

GHS Symbol:



#### **GHS Signal Word:**

Warning

#### GHS Hazard Determining Components:

Silicate Solution

Silver

#### GHS Hazard Statements for Health Hazards:

H303 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

### GHS Precautionary Statements - Prevention:

P264 Wash hands thoroughly after handling.
P280 Wear protective gloves. Wear eye protection.

#### GHS Precautionary Statements - Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P332 + P313 If skin irritation occurs: Get medical advice/attention.

P305 + P351 + P338 IF IN EYES: Remove contact lenses, if present and easy to do. Rinse cautiously with water for several minutes.

P312 IF SWALLOWED: Call a poison center or doctor if you feel unwell

P362 Take off contaminated clothing and wash before reuse.

GHS Storage/Disposal:

P501 Dispose in accordance with local, regional, national or international regulations

#### 3. COMPOSITION

| Chemical          | CAS No.   | EC No.    | Concentration | GHS Product Identifier   |
|-------------------|-----------|-----------|---------------|--|
| Silicate Solution | 1344-09-8 | 215-687-4 | 10.0-20.0 %   | H302 Acute Toxicity, Oral, Cat 4 H315 Skin Corrosion/Irritation, Cat 2 H319 Eye Damage/Eye Irritation, Cat 2A H335 STOT, SE; Respiratory Tract Irritation, Cat 3 |
| Silver Flake      | 7440-22-4 | 231-131-3 | 55.0-75.0 %   | None   |
| Water             | 7732-18-5 | NA        | 20.0-30.0 %   | N/A  |

#### Note

This product is a mixture and all powders are encapsulated.

#### 4. FIRST AID MEASURES

After eye contact: Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek immediate

medical attention, preferably with an ophthalmologist.

**After skin contact:** Immediately wipe excess material off skin with a dry cloth then wash with soap and water for at least 5 minutes. **After inhalation:** In case of inhalation due to spray mist, machining dust or dried particulate, remove source of exposure and

assure that victim is breathing. If not breathing, administer cardio-pulmonary resuscitation (CPR).

After ingestion: If swallowed, do not induce vomiting. If victim is conscious and alert, give 1-2 glasses of water to drink. Do not

give anything by mouth to an unconscious person. Seek medical attention immediately.

Medical Conditions Possibly Inhalation of product may aggravate existing chromic respiratory problems such as asthma, emphysema or

Aggravated by Exposure: bronchitis. Skin contact may aggravate existing skin disease.

#### 5. FIRE FIGHTING MEASURES

Flash Point: Not applicable

Flammable Limits: This material is non-combustible.

Extinguishing Media: This material is compatible with all extinguishing media.

Special Fire Fighting Procedures: Firefighters should wear NIOSH/MSHA approved positive pressure breathing apparatus with full face-piece and

full chemical resistant protective clothing. Dike area to prevent runoff and contamination of water sources.

Dispose of fire control water later.

Unusual Fire and Explosion Hazards: This material is non-combustible.

### 6. ACCIDENTAL RELEASE MEASURES

Personal Protection: Wear chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots. Use

NIOSH approved respirator where mist occurs.

Spill Cleanup: Mop up and neutralize liquid, then discharge to sewer in accordance with federal, state and local regulations or

permits. Flush area with water to complete cleanup. Exercise caution during neutralization as heat may be

generated.

## 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing spray mist. Keep container closed. Promptly clean

residue from closures with cloth dampened with water. Promptly clean up spills.

Storage: Store in an area that is cool, dry, well ventilated, away from combustible material, and away from ignition

sources. Keep containers closed. Store in clean plastic or stainless steel containers.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| Chemical          | CAS No.   | EC No.    | TLV (mg/m³)              | PEL (mg/m³)              |
|-------------------|-----------|-----------|--------------------------|--------------------------|
| Silicate Solution | 1344-09-8 | 215-687-4 | No available information | No available information |
| Silver Flake      | 7440-22-4 | 231-131-3 | 0.1                      | 0.01                     |
| Water             | 7732-18-5 | NA        | No available information | No available information |

**Engineering Controls:** Use with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within

direct access.

Respiratory Protection: This product is not considered respirable in either the liquid or cured forms. However, if the cured product is

polished, ground or chipped during processing, handling or use, powders may be released as airborne respirable particles. In these instances, appropriate personal protection equipment and local ventilation controls

must be employed. If exposure limits are exceeded and local ventilation is unavailable, a supplied-air respirator

or a self-contained NIOSH-approved dust and mist respirator is required.

Skin Protection: Wear body-covering protective clothing and gloves.

Eye Protection: Wear chemical goggles.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical here represent typical properties of this product. Contact Technical Sales for exact specifications.

Appearance: Paste Color: Silver

Odor Threshold: No available information

Odor: Odorless pH: 11.0-11.5 Specific Gravity, g/cc 2.20-2.30 Water Solubility: Soluble Melting Point: Not applicable **Boiling Point:** 100 °C Vapor Pressure: Not applicable Vapor Density (air=1): No data VOC Content: 0.00 lbs/gal Viscosity: Paste **Decomposition Temperature:** Not applicable Auto-ignition Temperature Not applicable Partition Coefficient: No data Flash Point: Not applicable Flammability: Not applicable

#### 10. STABILITY AND REACTIVITY

Evaporation Rate:

Chemical Stability: This material is stable under all conditions of use and storage.

Not applicable

Conditions to Avoid: Prolonged contact with aluminum, brass, copper, lead, and zinc may produce flammable hydrogen gas. Materials to Avoid: Gels and heats when mixed with acid. May react with ammonium salts resulting in evolution of ammonia gas.

Hazardous Decomposition Products: None. Hazardous Polymerization: Will not occur.

## 11. TOXICOLOGICAL INFORMATION

Component: CAS No. 1344-09-8, Silicate Solution Acute Toxicity:

> LD50 Oral, 1153 mg/kg (Rat) LD50, Inhalation, No Data LD50, Dermal, 4640 mg/kg (Rabbit)

Skin Corrosion/Irritation: Irritating to skin Serious Eye Damage/Irritation: Irritating to eyes Sensitization: Not sensitizing Mutagenicity: No data

Carcinogenicity: This product is not listed by IARC, NTP, OSHA, or ACGIH as a known or suspected carcinogen.

Reproductive Toxicity: No data

# **ECOLOGICAL INFORMATION**

Ecotoxity: This material is believed to be practically non-toxic to aquatic life. Biodegradation: This material is inorganic and not subject to biodegradation. Persistence: this material is believed to persist in the environment. Bioconcentration: This material is not expected to bioconcentrate in organisms.

Physical/Chemical: Sinks and mixes with water. Only water will evaporate from this material.

# 13. DISPOSAL CONSIDERATIONS

Disposal Method: Dispose in accordance with federal, state and local regulations and permits.

# 14. TRANSPORTATION INFORMATION

**DOT UN Status:** The material is not a regulated hazardous material for transportation.

# 15. REGULATORY INFORMATION

**U.S. Federal Regulations** 

CERCLA: No CERCLA reportable quantity has been established for this material.

TSCA: All ingredients of this material are listed on the TSCA inventory.

SARA Title III

Sections 302, 304, 313: This product does not contain any substances reportable under these sections.

Sections 311, 312:

| Hazard Classes          | Yes/No |
|-------------------------|--------|
| Fire Hazard             | No     |
| Reactivity Hazard       | No     |
| Pressure Hazard         | No     |
| Immediate Hazard        | Yes    |
| Delayed Hazard          | No     |
| •                       |        |
| International Inventory | Status |
| Canada (DSL)            | Yes    |
| Europe (EINECS/ELINCS)  | Yes    |
| Australia (AICS)        | Yes    |
| Japan (MITI)            | Yes    |
| South Korea (KECL)      | Yes    |

# 16. OTHER INFORMATION

| NFPA Ratings (scale 0 – 4) | Health, 1<br>Flammability, 0<br>Reactivity, 0<br>Personal Protection, C | 100<br>CO  |
|----------------------------|---|--|
| HMIS Ratings (scale 0 – 4) | Health, 1<br>Flammability, 0<br>Reactivity, 0<br>Personal Protection, C | HEALTH 1 FLAMMABILITY 0 REACTIVITY 0 PERSONAL PROTECTION C |

### **Key Legend Information**

ACGIH American Conference of Governmental Industrial Hygienists

ARD International Agency for Research on Cancer

CAS Chemical Abstract Service

CERCLA Comprehensive Environmental Response, Compensation & Liability Act

DSL Domestic Substance List EC European Commission

HMIS Hazardous Materials Identification System
IARC International Agency for Research on Cancer

ND Not Determined NE Not Established

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety & Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RE Repeat Exposure

SARA Superfund Amendments & Reauthorization Act
SARA Title III Emergency Planning & Community Right to Know Act

SARA Section 302 Extremely Hazardous Substances

SARA Section 304 Emergency Release

SARA Section 311 MSDS/List of Chemicals & Hazardous Inventory

SARA Section 312 Emergency & Hazardous Inventory
SARA Section 313 Toxic Chemicals & Release Reporting

SE Single Exposure

STEL Short Term Exposure Limit
STOT Specific Target Organ Toxicity
TLV Threshold Limit Value
TWA Time Weighted Average

**Disclaimer:** The information contained herein is based on data taken from sources believed to be both current and reliable at the time of publication. Aremoo Products, Inc. makes no warranty, expressed or implied, as to the accuracy of this MSDS and assumes no liability arising from its use by others. Compliance with all applicable Federal, State and Local laws and regulations remains the responsibility of the user.

# SAFETY DATA SHEET

**Product:** 598-A Revision Date: 6/01/2015

### 1. MATERIAL IDENTIFICATION

Product Name: Pyro-Duct 598-A

**Product Description:** Gray, Odorless Paste

Product Use: High Temperature Conductive Adhesive

Manufacturer: Aremco Products, Inc.

707-B Executive Blvd. Valley Cottage, NY 10989

**Telephone:** 845-268-0039

**Emergency Phone:** 845-268-0039 or Infotrac (24/7) 800-535-5053

## 2. HAZARDS IDENTIFICATION

GHS Classification:

Eye Irritation Category 2A Skin Irritation Category 2

GHS Symbol:



### GHS Signal Word:

Warning

### GHS Hazard Determining Components:

Silicate Solution

Nickel

### GHS Hazard Statements for Health Hazards:

H303 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

### GHS Precautionary Statements - Prevention:

P264 Wash hands thoroughly after handling.
P280 Wear protective gloves. Wear eye protection.

### GHS Precautionary Statements - Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P332 + P313 If skin irritation occurs: Get medical advice/attention.

P305 + P351 + P338 IF IN EYES: Remove contact lenses, if present and easy to do. Rinse cautiously with water for several minutes.

P312 IF SWALLOWED: Call a poison center or doctor if you feel unwell

P362 Take off contaminated clothing and wash before reuse.

GHS Storage/Disposal:

P501 Dispose in accordance with local, regional, national or international regulations

## **COMPOSITION**

| Chemical          | CAS No.   | EC No.    | Concentration | GHS Product Identifier   |
|-------------------|-----------|-----------|---------------|--|
| Nickel            | 7440-02-0 | 231-111-4 | 50.0-70.0%    | H228 Flammable Solids, Cat 2 H317 Sensitization, Skin, Cat 1 H351 Suspected of Causing Cancer, Cat 2 H372 STOT, RE, Causes Damage to Organs, Cat 1               |
| Silicate Solution | 1312-76-1 | 215-687-4 | 10.0-20.0%    | H302 Acute Toxicity, Oral, Cat 4 H315 Skin Corrosion/Irritation, Cat 2 H319 Eye Damage/Eye Irritation, Cat 2A H335 STOT, SE; Respiratory Tract Irritation, Cat 3 |
| Water             | 7732-18-5 | NA        | 20.0-30.0%    | N/A  |

#### Note

This product is a mixture and all powders are encapsulated.

### 4. FIRST AID MEASURES

After eye contact: Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek immediate

medical attention, preferably with an ophthalmologist.

Immediately wipe excess material off skin with a dry cloth then wash with soap and water for at least 5 minutes. After skin contact: After inhalation:

In case of inhalation due to spray mist, machining dust or dried particulate, remove source of exposure and

assure that victim is breathing. If not breathing, administer cardio-pulmonary resuscitation (CPR). After ingestion: If swallowed, do not induce vomiting. If victim is conscious and alert, give 1-2 glasses of water to drink. Do not

give anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation of product may aggravate existing chromic respiratory problems such as asthma, emphysema or Medical Conditions Possibly

bronchitis. Skin contact may aggravate existing skin disease. Aggravated by Exposure:

### 5. FIRE FIGHTING MEASURES

Flash Point: Not applicable

Flammable Limits: This material is non-combustible.

Extinguishing Media: This material is compatible with all extinguishing media.

Special Fire Fighting Procedures: Firefighters should wear NIOSH/MSHA approved positive pressure breathing apparatus with full face-piece and

full chemical resistant protective clothing. Dike area to prevent runoff and contamination of water sources.

Dispose of fire control water later.

Unusual Fire and Explosion Hazards: This material is non-combustible.

## 6. ACCIDENTAL RELEASE MEASURES

Personal Protection: Wear chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots. Use

NIOSH approved respirator where mist occurs.

Spill Cleanup: Mop up and neutralize liquid, then discharge to sewer in accordance with federal, state and local regulations or

permits. Flush area with water to complete cleanup. Exercise caution during neutralization as heat may be

generated.

### 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing spray mist. Keep container closed. Promptly

clean residue from closures with cloth dampened with water. Promptly clean up spills.

Storage: Store in an area that is cool, dry, well ventilated, away from combustible material, and away from ignition

sources. Keep containers closed. Store in clean plastic or stainless steel containers.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| Chemical          | CAS No.   | EC No.    | TLV (mg/m³)              | PEL (mg/m³)              |
|-------------------|-----------|-----------|--------------------------|--------------------------|
| Nickel Flake      | 7440-02-0 | 231-111-4 | 1.5                      | Not established          |
| Silicate Solution | 1344-09-8 | 215-687-4 | No available information | No available information |
| Water             | 7732-18-5 | N/A       | No available information | No available information |

Engineering Controls: Use with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within

direct access

Respiratory Protection: This product is not considered respirable in either the liquid or cured forms. However, if the cured product is

polished, ground or chipped during processing, handling or use, powders may be released as airborne respirable particles. In these instances, appropriate personal protection equipment and local ventilation controls must be employed. If exposure limits are exceeded and local ventilation is unavailable, a supplied-air

respirator or a self-contained NIOSH-approved dust and mist respirator is required.

**Skin Protection:** Wear body-covering protective clothing and gloves.

Eye Protection: Wear chemical goggles.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical here represent typical properties of this product. Contact Technical Sales for exact specifications.

Appearance: Paste Color: Gray

Odor Threshold: No available information

Odor: Odorless pH: 11.0-11.5 Specific Gravity, g/cc 2.60-2.80 Water Solubility: Soluble Melting Point: Not applicable **Boiling Point:** 100 °C Vapor Pressure: Not applicable Vapor Density (air=1): No data **VOC Content:** 0.00 lbs/gal Viscosity: > 100,000 cPDecomposition Temperature: Not applicable Auto-ignition Temperature Not applicable Partition Coefficient: No data Flash Point: Not applicable Not applicable Flammability:

## 10. STABILITY AND REACTIVITY

Evaporation Rate:

Chemical Stability: This material is stable under all conditions of use and storage.

Not applicable

Conditions to Avoid:

Prolonged contact with aluminum, brass, copper, lead, and zinc may produce flammable hydrogen gas.

Materials to Avoid:

Gels and heats when mixed with acid. May react with ammonium salts resulting in evolution of ammonia gas.

Hazardous Decomposition Products: None.

Hazardous Polymerization: Will not occur.

### 11. TOXICOLOGICAL INFORMATION

Acute Toxicity: Component: CAS No. 1344-09-8, Silicate Solution

LD50 Oral, 1153 mg/kg (Rat) LD50, Inhalation, No Data

LD50, Dermal, 4640 mg/kg (Rabbit)

Skin Corrosion/Irritation:
Serious Eye Damage/Irritation:
Sensitization:
Mutagenicity:

Irritating to skin
Irritating to eyes
Not sensitizing
No data

Carcinogenicity: This product is not listed by IARC, NTP, OSHA, or ACGIH as a known or suspected carcinogen.

Reproductive Toxicity: No data

## 12. ECOLOGICAL INFORMATION

Ecotoxity:This material is believed to be practically non-toxic to aquatic life.Biodegradation:This material is inorganic and not subject to biodegradation.Persistence:this material is believed to persist in the environment.Bioconcentration:This material is not expected to bioconcentrate in organisms.

# 13. DISPOSAL CONSIDERATIONS

Disposal Method: Dispose in accordance with federal, state and local regulations and permits.

## 14. TRANSPORTATION INFORMATION

**DOT UN Status:** The material is not a regulated hazardous material for transportation.

# 15. REGULATORY INFORMATION

**U.S. Federal Regulations** 

CERCLA: No CERCLA reportable quantity has been established for this material.

**TSCA:** All ingredients of this material are listed on the TSCA inventory.

SARA Title III

Sections 302, 304, 313: This product does not contain any substances reportable under these sections.

Sections 311, 312:

| Hazard Classes          | Yes/No |
|-------------------------|--------|
| Fire Hazard             | No     |
| Reactivity Hazard       | No     |
| Pressure Hazard         | No     |
| Immediate Hazard        | Yes    |
| Delayed Hazard          | No     |
|                         |        |
| International Inventory | Status |
| Canada (DSL)            | Yes    |
| Europe (EINECS/ELINCS)  | Yes    |
| Australia (AICS)        | Yes    |
| Japan (MITI)            | Yes    |
| South Korea (KECL)      | Yes    |

# 16. OTHER INFORMATION

| NFPA Ratings (scale 0 – 4) | Health, 1<br>Flammability, 0<br>Reactivity, 0<br>Personal Protection, C | 100  |
|----------------------------|---|--|
| HMIS Ratings (scale 0 – 4) | Health, 1<br>Flammability, 0<br>Reactivity, 0<br>Personal Protection, C | HEALTH 1 FLAMMABILITY 0 REACTIVITY 0 PERSONAL PROTECTION C |

## **Key Legend Information**

ACGIH American Conference of Governmental Industrial Hygienists

ARD International Agency for Research on Cancer

CAS Chemical Abstract Service

CERCLA Comprehensive Environmental Response, Compensation & Liability Act

DSL Domestic Substance List EC European Commission

HMIS Hazardous Materials Identification System
IARC International Agency for Research on Cancer

ND Not Determined NE Not Established

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety & Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RE Repeat Exposure

SARA Superfund Amendments & Reauthorization Act
SARA Title III Emergency Planning & Community Right to Know Act

SARA Section 302 Extremely Hazardous Substances

SARA Section 304 Emergency Release

SARA Section 311 MSDS/List of Chemicals & Hazardous Inventory

SARA Section 312 Emergency & Hazardous Inventory
SARA Section 313 Toxic Chemicals & Release Reporting

SE Single Exposure

STEL Short Term Exposure Limit
STOT Specific Target Organ Toxicity
TLV Threshold Limit Value
TWA Time Weighted Average

**Disclaimer:** The information contained herein is based on data taken from sources believed to be both current and reliable at the time of publication. Aremoo Products, Inc. makes no warranty, expressed or implied, as to the accuracy of this MSDS and assumes no liability arising from its use by others. Compliance with all applicable Federal, State and Local laws and regulations remains the responsibility of the user.