# SAFETY DATA SHEET

Product: CP3015-SS 6/01/2015 Revision Date:

### **MATERIAL IDENTIFICATION**

**Product Name:** Corr-Paint CP3015-SS

**Product Description:** Metallic-Grey, Odorless Liquid **Product Use:** High Temperature Metallic Coating

Manufacturer: Aremco Products, Inc. 707-B Executive Blvd.

Valley Cottage, NY 10989

Telephone: 845-268-0039

**Emergency Phone:** 845-268-0039 or Infotrac (24/7) 800-535-5053

## 2. HAZARDS IDENTIFICATION

GHS Classification:

Eve Irritation Category 2A Skin Irritation Category 2

GHS Symbol:



GHS Signal Word:

Warning

GHS Hazard Determining Components:

Lithium Polysilicate Stainless Steel

Magnesium Silicate Hydrate

GHS Hazard Statements for Health Hazards:

H315 Causes skin irritation. H319 Causes serious eye irritation.

GHS Precautionary Statements - Prevention:

P264 Wash hands thoroughly after handling P280 Wear protective gloves. Wear eye protection.

GHS Precautionary Statements - Response:

P302+P352 IF ON SKIN: Wash with plenty of soap and water P332+P313 If skin irritation occurs, get medical attention Take off contaminated clothing and wash before reuse P362

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses

if present and easy to do and continue rinsing

P313+P337 If eye irritation persists, get medical attention

GHS Precautionary Statements - Storage/Disposal:

Dispose in accordance with local, regional, national or international regulations. P501

### 3. COMPOSITION

Chemical Name	CAS No.	EC No.	Concentration	GHS Product Identifier
Lithium Polysilicate	12627-14-4	235-730-0	10.0-20.0 %	H315 Skin Corrosion/Irritation, Cat 2 H319 Serious Eye Damage/Eye Irritation, Cat 2A H335 STOT, SE; Respiratory Tract Irritation, Cat 3
Stainless Steel Flake	65997-19-5	NE	15.0-25.0%	H317 Sensitization, Skin, Cat 1 H334 Sensitization, Respiratory, Cat 1 H351 Suspected of Causing Cancer, Cat 2 H372 STOT, RE, Causes Damage to Organs, Cat 1 H413 Aquatic Chronic, Cat 4
Magnesium Silicate, Hydrate	14807-96-6	238-877-9	1.0-10.0 %	None
Water	7732-18-5	NA	40.0-60.0 %	N/A

#### Notes

1. This product is a mixture and all powders are encapsulated.

2. Stainless steel flake is an alloy of iron, chromium, nickel and molybdenum. Nickel is less than 12% of the alloy.

### 4. FIRST AID MEASURES

After eye contact: Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek immediate

medical attention, preferably with an ophthalmologist.

After skin contact: Immediately wipe excess material off skin with a dry cloth then wash with soap and water for at least 5 minutes.

After inhalation: In case of inhalation due to spray mist, machining dust or dried particulate, remove source of exposure and

assure that victim is breathing. If not breathing, administer cardio-pulmonary resuscitation (CPR).

After ingestion: If swallowed, do not induce vomiting. If victim is conscious and alert, give 1-2 glasses of water to drink. Do not

give anything by mouth to an unconscious person. Seek medical attention immediately.

Medical Conditions Possibly Inhalation of product may aggravate existing chromic respiratory problems such as asthma, emphysema or

Aggravated by Exposure: bronchitis. Skin contact may aggravate existing skin disease.

## 5. FIRE FIGHTING MEASURES

Flash Point: Not applicable

Flammable Limits: This material is non-combustible.

Extinguishing Media: This material is compatible with all extinguishing media.

Special Fire Fighting Procedures: Firefighters should wear NIOSH/MSHA approved positive pressure breathing apparatus with full face-piece and

full chemical resistant protective clothing. Dike area to prevent runoff and contamination of water sources.

Dispose of fire control water later.

Unusual Fire and Explosion Hazards: This material is non-combustible.

# **6. ACCIDENTAL RELEASE MEASURES**

Personal Protection: Wear chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots. Use

NIOSH approved respirator where mist occurs.

Spill Cleanup: Mop up and neutralize liquid, then discharge to sewer in accordance with federal, state and local regulations or

permits. Flush area with water to complete cleanup. Exercise caution during neutralization as heat may be

generated.

### 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing spray mist. Keep container closed. Promptly clean

residue from closures with cloth dampened with water. Promptly clean up spills.

Storage: Store in an area that is cool, dry, well ventilated, away from combustible material, and away from ignition

sources. Keep containers closed. Store in clean plastic or stainless steel containers.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical	CAS No.	EC No.	TLV (mg/m³)	PEL (mg/m³)
Lithium Polysilicate	12627-14-4	235-730-0	No available information	No available information
Stainless Steel Flake	65997-19-5	NE	0.5	1.0
Magnesium Silicate, Hydrate	14807-96-6	238-877-9	2	2
Water	7732-18-5	NA	No available information	No available information

Engineering Controls: Use with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within

direct access.

Respiratory Protection: If exposure limits are exceeded and local ventilation is unavailable, a supplied-air respirator or a self-contained

NIOSH-approved dust and mist respirator is required.

**Skin Protection:** Wear body-covering protective clothing and gloves.

**Eye Protection:** Wear chemical goggles.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical here represent typical properties of this product. Contact Technical Sales for exact specifications.

Appearance: Liquid Metallic Grey Color: Odor Threshold (ppm): Not applicable Odor: Odorless pH: 10.0-11.0 Specific Gravity: 1.45-1.50 g/cc Water Solubility: Soluble Melting Point: Not applicable Boiling Point: 100 °C Vapor Pressure: Not applicable Vapor Density (air=1): No data VOC Content, g/l: 0.00 lbs/gal Viscosity: 200-500 cP **Decomposition Temperature:** Not applicable Auto-ignition Temperature Not applicable Partition Coefficient: No data Flash Point: Not applicable Flammability: Not applicable Not applicable Evaporation Rate:

## 10. STABILITY AND REACTIVITY

Chemical Stability: This material is stable under all conditions of use and storage.

Conditions to Avoid: See section on "Material to Avoid"...

Materials to Avoid: Reacts with aluminum, tin and their alloys evolving hydrogen gas that can form and explosive mixture with air.

Can react violently if in contact with acids. Can react with sugar residues to form carbon monoxide.

Hazardous Decomposition Products: None with proper storage and handling.

Hazardous Polymerization: Will not occur.

### 11. TOXICOLOGICAL INFORMATION

Inhalation:

Acute Toxicity: Component: CAS No. 12627-14-4, Lithium Polysilicate

Ingestion: Lithium compounds may damage the central nervous system. A large dose may cause headache, nausea,

dizziness, convulsions, kidney damage.

Mist is irritating to the respiratory tract.

**Skin Contact:** Repeated and/or prolonged skin contact may cause slight irritation.

Eye Contact: Liquid or mist may cause discomfort and mild irritation.

Skin Corrosion/Irritation:
Serious Eye Damage/Irritation:
Sensitization:
Not sensitizing
Mutagenicity:
Irritating to skin
Irritating to eyes
Not sensitizing
No data

Carcinogenicity: This product is not listed by IARC, NTP, OSHA, or ACGIH as a known or suspected carcinogen.

Reproductive Toxicity: Lithium compounds – teratogenic effects have been observed in laboratory animals.

Component: CAS No. 65997-19-5, Stainless Steel Flake

The stainless steel flake is an alloy of chromium, nickel and cobalt, and we are unaware of any toxicological tests of 316 stainless steel. Nickel and cobalt are less than 10% of the alloy. Results of toxicological studies suggest that alloys containing 40% or less nickel are not carcinogenic even by potential routes of administration.

## 12. ECOLOGICAL INFORMATION

**Toxicity:** Lithium compounds – no data.

Persistence & Degradability: Inorganic. Soluble silicates, upon dilution, rapidly depolymerize into molecular species indistinguishable from

natural dissolved silica.

Bioaccumulative Potential: Inorganic. The substance has no potential for bioaccumulation.

Mobility in Soil: Not applicable.

Results of PBT or vPvB Assessment: Not classified as PBT or vPvB.

Other Adverse Effects: The alkalinity of this material will have a local effect on ecosystems sensitive to changes in pH.

# 13. DISPOSAL CONSIDERATIONS

Disposal Method: Dispose in accordance with federal, state and local regulations and permits.

### 14. TRANSPORTATION INFORMATION

**DOT UN Status:** The material is not a regulated hazardous material for transportation.

## 15. REGULATORY INFORMATION

#### **U.S. Federal Regulations**

CERCLA: No CERCLA reportable quantity has been established for this material.

TSCA: All ingredients of this material are listed on the TSCA inventory.

SARA Title III

Sections 302, 304, 313: This product does not contain any substances reportable under these sections.

Sections 311, 312:

Hazard Classes	Yes/No
Fire Hazard	No
Reactivity Hazard	No
Pressure Hazard	No
Immediate Hazard	Yes
Delayed Hazard	No
•	
International Inventory	Status
International Inventory Canada (DSL)	Status Yes
Canada (DSL)	Yes
Canada (DSL) Europe (EINECS/ELINCS)	Yes Yes
Canada (DSL) Europe (EINECS/ELINCS) Australia (AICS)	Yes Yes Yes

### **16. OTHER INFORMATION**

NFPA Ratings (scale 0 – 4)	Health, 1 Flammability, 0 Reactivity, 0 Personal Protection, C	CO
HMIS Ratings (scale 0 – 4)	Health, 1 Flammability, 0 Reactivity, 0 Personal Protection, C	HEALTH 1 FLAMMABILITY 0 REACTIVITY 0 PERSONAL PROTECTION C

#### **Key Legend Information**

ACGIH American Conference of Governmental Industrial Hygienists

ARD International Agency for Research on Cancer

CAS Chemical Abstract Service

CERCLA Comprehensive Environmental Response, Compensation & Liability Act

DSL Domestic Substance List EC European Commission

HMIS Hazardous Materials Identification System

IARC International Agency for Research on Cancer

ND Not Determined NE Not Established

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety & Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RE Repeat Exposure

SARA Superfund Amendments & Reauthorization Act
SARA Title III Emergency Planning & Community Right to Know Act

SARA Section 302 Extremely Hazardous Substances

SARA Section 304 Emergency Release

SARA Section 311 MSDS/List of Chemicals & Hazardous Inventory

SARA Section 312 Emergency & Hazardous Inventory
SARA Section 313 Toxic Chemicals & Release Reporting

SE Single Exposure

STELShort Term Exposure LimitSTOTSpecific Target Organ ToxicityTLVThreshold Limit ValueTWATime Weighted Average

**Disclaimer:** The information contained herein is based on data taken from sources believed to be both current and reliable at the time of publication. Aremco Products, Inc. makes no warranty, expressed or implied, as to the accuracy of this MSDS and assumes no liability arising from its use by others. Compliance with all applicable Federal, State and Local laws and regulations remains the responsibility of the user.