SAFETY DATA SHEET

Product:CP4040Revision Date:6/01/2015

1. MATERIAL IDENTIFICATION

Product Name:	Corr-Paint CP4040
Product Description:	Silicone-Ceramic Coating, White Liquid, And Solvent Odor
Product Use:	High Temperature Protective Coating
Manufacturer:	Aremco Products, Inc. 707-B Executive Blvd. Valley Cottage, NY 10989
Telephone:	845-268-0039
Emergency Phone:	845-268-0039 or Infotrac (24/7) 800-535-5053

2. HAZARDS IDENTIFICATION

GHS Classification: Skin Irritation Eye Irritation

Category 2 Category 2



GHS Signal Word:

GHS Symbols:

Warning

GHS Hazard Determining Components:

Silicon Emulsion Magnesium Silicate Hydrate Mica Titanium Dioxide Trizinc Bis (Orthophosphate) Zinc Oxide

GHS Hazard Statements for Health Hazards: H315 Causes skin irritation

H319 Causes serious eye irritation

GHS Precautionary Statements - Prevention:

P233 P280 Keep container tightly closed.

Wear protective gloves/eye protection/face protection.

GHS Precautionary Statements - Response:

P312	Call a poison center or physician if you feel unwell.
P303 + P361 + P353	IF ON SKIN: Remove contaminated clothing and rinse skin with water.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.

GHS Precautionary Statements – Storage & Disposal:

P403	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

3. COMPOSITION

Ingredient	CAS No.	EC No.	Concentration	GHS Product Identifier
Magnesium Silicate, Hydrate	14807-96-6	238-877-9	1.0-5.0%	None
Mica	12001-26-2	301-127-6	5.0-10.0%	H335 STOT, SE; Respiratory Tract Irritation, Cat 3
Titanium Dioxide	13463-67-7	236-675-5	1.0-5.0%	None
Trizinc Bis (Orthophosphate)	7779-90-0	231-944-3	< 4.0%	H400 Aquatic Acute, Cat 1 H410 Aquatic Chronic, Cat 1
Zinc Oxide	1314-13-2	215-222-5	< 1.0%	H400 Aquatic Acute, Cat 1 H410 Aquatic Chronic, Cat 1
Water	7732-18-5	231-791-2	20.0-30.0%	N/A
Silicone Emulsion Including:			30.0-50.0%	H226 Flammable Liquids, Cat 3 H315 Skin Irritation, Cat 2 H319 Eye Irritation, Cat 2
Water (40.0-50.0%)	7732-18-5	NA		N/A
Xylene (5.0-10.0%)	1330-20-7	215-535-7		H226 Flammable Liquids, Cat 3 H312 Acute Toxicity, Dermal, Cat 4 H315 Skin Corrosion/Irritation, Cat 2 H332 Acute toxicity, Inhalation, Cat 4
Methanol (0.5-1.0%)	67-56-1	200-659-6		H225 Flammable Liquids, Cat 2 H301 Acute Toxicity, Oral, Cat 3 H311 Acute Toxicity, Dermal, Cat 3 H331 Acute Toxicity, Inhalation, Cat 3 H370 STOT SE, Oral, Skin, Dermal, Cat 1
1-Propanol, 2-Methyl- (2.5-5.0%)	78-83-1	201-148-0		H226 Flammable Liquids, Cat 3 H315 Skin Corrosion/Irritation, Cat 2 H318 Serious Eye Damage/Eye Irritation, Cat 1 H335 STOT, SE; Respiratory Tract Irritation, Cat 3 H336 STOT, SE; Narcotic Effects, Cat 3
Ethyl Benzene (1.0-2.5%)	100-41-4	202-849-4		H225 Flammable Liquids, Cat 2 H332 Acute toxicity, Inhalation, Cat 4

4. FIRST AID MEASURES

Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek immediate medical attention, preferably with an ophthalmologist.
Immediately wipe excess material off skin with a dry cloth then wash with soap and water for at least 5 minutes.
In case of inhalation due to <u>spray mist</u> , remove source of exposure and assure that victim is breathing. If not breathing, administer cardio-pulmonary resuscitation (CPR).
If swallowed, do not induce vomiting. If victim is conscious and alert, give 1-2 glasses of water to drink. Do not give anything by mouth to an unconscious person. Seek medical attention immediately.
Inhalation of product may aggravate existing chromic respiratory problems such as asthma, emphysema or bronchitis. Skin contact may aggravate existing skin disease.

5. FIRE FIGHTING MEASURES

Flash Point:	> 200 °F
Flammable Limits:	Not measured.
Extinguishing Media:	Foam, carbon dioxide, dry powder, water spray.
Special Fire Fighting Procedures:	Firefighters should wear NIOSH/MSHA approved positive pressure breathing apparatus with full face-piece and full chemical resistant protective clothing. Dike area to prevent runoff and contamination of water sources.
	Dispose of fire control water later.
Unusual Fire and Explosion Hazards	s: This material can release carbon monoxide, carbon dioxide, and silicon dioxide.

6. ACCIDENTAL RELEASE MEASURES

Personal Protection:	Wear chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots. Use
Spill Cleanup:	NIOSH approved respirator where mist occurs. Ensure adequate ventilation. Take up with absorbent material (e.g., sand). Dispose of absorbed material in accordance with federal, state and local regulations or permits. Flush area with water to complete cleanup.

7. HANDLING AND STORAGE

Handling:

Ensure adequate ventilation. Avoid contact with eyes, skin and clothing. Avoid breathing spray mist. Keep container closed. Promptly clean residue from closures with cloth dampened with water. Promptly clean up spills.

Storage:

Store in an area that is cool, dry, well ventilated, away from combustible material, and away from ignition sources. Keep containers closed. Store in clean plastic or stainless steel containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredient	CAS No.	EC No.	TLV (mg/m ³)	PEL (mg/m ³)
Magnesium Silicate, Hydrate	14807-96-6	238-877-9	2	2
Mica	12001-26-2	310-127-6	Not established	Not established
Titanium Dioxide	13463-67-7	236-675-5	10	10
Trizinc Bis (Orthophosphate)	7779-90-0	231-944-3	2	5
Zinc Oxide	1314-13-2	215-222-5	2	5
Water	7732-18-5	NA	N/A	N/A
Silicone Emulsion Including:				
Water	7732-18-5	NA	N/A	N/A
Xylene	1330-20-7	215-535-7	440	440
Methanol	67-56-1	200-659-6	270	270
1-Propanol, 2-Methyl-	78-83-1	201-148-0	310	310
Ethyl Benzene	100-41-4	202-849-4	N/D	N/D

Engineering Controls:	Use with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within direct access.
Respiratory Protection:	If exposure limits are exceeded and local ventilation is unavailable, a supplied-air respirator or a self-contained NIOSH-approved dust and mist respirator is required.
Skin Protection:	Wear body-covering protective clothing and gloves. A protective glove made of fluorinated rubber is recommended.
Eye Protection:	Wear chemical goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical here represent typical properties of this product. Contact Technical Sales for exact specifications.

Appearance: Color:	Liquid White
Odor threshold:	No available information
Odor:	Xylene
pH:	6-8
Specific Gravity, g/cc	1.27
Water Solubility:	Miscible
Melting Point Range:	No available information
Boiling Point Range:	212 °F
Vapor Pressure:	No available information
Vapor Density (air=1):	No available information
VOC Content, g/I:	0.98 lbs/gal
Viscosity:	400-900 cP
Decomposition temperature:	No available information
Auto-ignition temperature	No available information
Partition coefficient:	No available information
Flash point:	> 200 °F
Flammability:	No available information
Evaporation rate:	No available information

10. STABILITY AND REACTIVITY

Chemical Stability: Conditions to Avoid: Materials to Avoid: Hazardous Decomposition Products: None with proper storage and handling. Hazardous Polymerization:

This material is stable under all conditions of use and storage. Contact with strong oxidizing agents. Reacts with oxidizing agents. Will not occur.

11. TOXICOLOGICAL INFORMATION

Note:	Due to the composition of the product it cannot be excluded that prolonged and repeated contact will result in irritation of the eyes. Proper use provided, no adverse health effects have been observed or have come to our attention.
Acute Toxicity Data:	Not available
Chronic Toxicity Data:	Not available
NTP Listing:	Not listed
IARC Listing:	Not listed

12. ECOLOGICAL INFORMATION

Ecotoxity: Environmental Fate:

Not tested, but should not be allowed to enter soil or waterways. Not tested.

13. DISPOSAL CONSIDERATIONS

Disposal Method:

Dispose in accordance with federal, state and local regulations and permits.

14. TRANSPORTATION INFORMATION

DOT UN Status:

The material is not a regulated hazardous material for transportation.

15. REGULATORY INFORMATION

U.S. Federal Regulations

CERCLA:	CAS No.Lbs1330-20-0100	_	
TSCA:	All ingredients of this materia	al are listed on the	TSCA inventory.
SARA Section 313:	<u>Components</u> Methanol Xylenes (o-, m-, p- Isomers) Ethyl benzene	CAS No. 67-56-1 1330-20-7 100-41-4	Concentration (%) 0-0 (0.87) 0-0 (7.27) 0-0 (2.42)
SARA Sections 311, 312:	Hazard Classes Fire Reactivity Pressure Immediate Delayed	Yes/No No No Yes No	
International Inventory	Country Canada (DSL) Europe (EINECS/ELINCS) Australia (AICS) Japan (MITI) South Korea (KECL)	Status Yes Yes Yes Yes Yes	

16. OTHER INFORMATION

NFPA Ratings (scale 0 – 4)	Health, 1 Flammability, 0 Reactivity, 0 Personal Protection, G	
HMIS Ratings (scale 0 – 4)	Health, 1 Flammability, 0 Reactivity, 0 Personal Protection, G	HEALTH 1 FLAMMANNUTT 0 RAATTUATY 0 PERSONAL PROTECTION G

Key Legend Information

Disclaimer: The information contained herein is based on data taken from sources believed to be both current and reliable at the time of publication. Aremco Products, Inc. makes no warranty, expressed or implied, as to the accuracy of this MSDS and assumes no liability arising from its use by others. Compliance with all applicable Federal, State and Local laws and regulations remains the responsibility of the user.