# MATERIAL SAFETY DATA SHEET

Product: Ceramacoat 512-N

Revision Date: 1/27/2009

## 1. MATERIAL IDENTIFICATION

Product Name: Ceramacoat 512-N

Product Description:Off-White, Viscous, and Odorless PasteProduct Use:High Temperature Adhesive/Coating System

**Manufacturer:** Aremco Products, Inc.

707-B Executive Blvd. Valley Cottage, NY 10989

**Telephone**: 845-268-0039

**Emergency Phone:** 845-268-0039 or Infotrac (24/7) 800-535-5053

### 2. COMPOSITION

Ingredient	CAS#	ACGIH TLV (mg/m <sup>3</sup> )	OSHA PEL (mg/m <sup>3</sup> )
Quartz, Crystalline Silica	14808-60-7	0.1	0.1
Aluminum Oxide	1344-28-1	10	15
Titanium Dioxide	13463-67-7	10	10
Iron Oxide (trace)	1309-37-1	10	N/D
Alumino-Silicate, Hydrous	1332-58-7	N/E	N/E
Alumino-Silicate Fiber, Vitreous	142844-00-6	N/E	N/E
Silicate Solution	1344-09-8	N/E	N/E
Water	7732-18-5	N/A	N/A

#### Notes:

1) This product is a liquid mixture and all powders are encapsulated.

2) Exposure values shown for guidance only. Please follow applicable regulations.

## 3. HAZARDS IDENTIFICATION

Emergency Overview: Off-white, odorless, paste. May cause moderate irritation to eyes, skin, and digestive tract.

Eye Contact:May cause moderate irritation to the eyes.Skin Contact:May cause moderate irritation to the skin.

Inhalation Acute:Mists may cause irritation to upper respiratory track.Ingestion Acute:May cause irritation to mouth, esophagus, and stomach.

Chronic Hazards: Silica: This product contains crystalline silica; once inhaled, cristobalite can remain in the lungs

causing scarring, stiffening and difficulty breathing. The most common type of silicosis develops following repeated inhalation over time. Repeated inhalation of crystalline silica can also increase the risks of developing respiratory cancer. Avoid dust creation. Do not inhale dusts from this product. Do not use compressed air or dry sweeping to remove dusts from the work area. Use wet clean-up methods to remove dusts. IARC and NTP classify respirable crystalline silica as a confirmed or known human carcinogen. Although OSHA has not promulgated a specific standard for crystalline silica, materials that contain >= 0.1% crystalline silica should be treated as a confirmed carcinogen for

hazard communication purposes.

Physical Hazards: Spilled material is slippery. Dries to form a glassy film that can cut skin.

HMIS:

Health: 1
Flammability: 0
Reactivity: 0
Personal Protection: C

### 4. FIRST AID MEASURES

#### Eye Exposure:

Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek immediate medical attention, preferably with an ophthalmologist. If a physician is not immediately available, eye irrigation should be continued for an additional 15 minutes.

#### Skin Exposure:

Immediately wipe excess material off skin with a dry cloth then wash with plenty of soap and water for at least 5 minutes. See medical attention if irritation develops or persists. Remove contaminated clothing and shoes and clean thoroughly before re-use.

#### Inhalation:

Remove from immediate source of exposure and assure that victim is breathing. If not breathing, administer cardio-pulmonary resuscitation (CPR). If breathing is difficult, administer oxygen if available. Seek medical attention.

#### Ingestion

If swallowed, do not induce vomiting. If victim is conscious and alert, give 1-2 glasses of water to drink. Do not give anything by mouth to an unconscious person. Seek medical attention immediately. Do not leave victim unattended. To prevent aspiration of swallowed product, lay victim on side with head lower than waist. Vomiting may occur spontaneously. If vomiting occurs and the victim is conscious, give water to further dilute the chemical.

# Medical Conditions Possibly Aggravated by Exposure:

Inhalation of product may aggravate existing chromic respiratory problems such as asthma, emphysema or bronchitis. Skin contact may aggravate existing skin disease.

## 5. FIRE FIGHTING MEASURES

Flash Point: Not applicable

Flammable Limits: This material is non-combustible.

Extinguishing Media: This material is compatible with all extinguishing media.

Special Fire Fighting Procedures: Firefighters should wear NIOSH/MSHA approved positive pressure breathing apparatus with full face-

piece and full chemical resistant protective clothing. Dike area to prevent runoff and contamination of

water sources. Dispose of fire control water later.

Unusual Fire and Explosion Hazards: This material is non-combustible.

### 6. ACCIDENTAL RELEASE MEASURES

Personal Protection: Wear chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber

boots. Use NIOSH approved respirator where mist occurs.

Spill Cleanup: Mop up and neutralize liquid, then discharge to sewer in accordance with federal, state and local

regulations or permits. Flush area with water to complete cleanup. Exercise caution during

neutralization as heat may be generated.

### 7. HANDLING AND STORAGE

Storage:

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing spray mist. Keep container closed.

Promptly clean residue from closures with cloth dampened with water. Promptly clean up spills. Store in an area that is cool, dry, well ventilated, away from combustible material, and away from

ignition sources. Keep containers closed. Store in clean plastic or stainless steel containers.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should

be within direct access.

Respiratory Protection: This product is not considered respirable in either the liquid or cured forms. However, if the cured

product is polished, ground or chipped during processing, handling or use, powders may be released as airborne respirable particles. In these instances, appropriate personal protection equipment and local ventilation controls must be employed. If exposure limits are exceeded and local ventilation is unavailable, a supplied-air respirator or a self-contained NIOSH-approved dust and mist respirator is

required.

**Skin Protection:** Wear body-covering protective clothing and gloves.

Eye Protection: Wear chemical goggles.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical here represent typical properties of this product. Contact Technical Sales for exact specifications.

Viscous Paste Appearance: Color: Off-White Odor: Odorless pH: > 11.0 Specific Gravity, g/cc 2.0 Soluble Water Solubility: Melting Point Range: Not available Boiling Point Range: Not available Vapor Pressure: Not available Vapor Density (air=1): Not available VOC Content, g/l: 0.00

# 10. STABILITY AND REACTIVITY

Chemical Stability: This material is stable under all conditions of use and storage.

Conditions to Avoid: Flammable hydrogen gas may be produced on contact with aluminum, tin, lead, and zinc.

Materials to Avoid: Gels and generates heat when mixed with acid. May react with ammonium salts resulting in evolution

of ammonia gas.

Hazardous Decomposition Products: None.

Hazardous Polymerization: Will not occur.

## 11. TOXICOLOGICAL INFORMATION

#### RTECS Toxicity Data for Product Components:

Ingredient	CAS#	NIOSH (RTECS) #
Silicate Solution	1344-09-8	VV9365000
Aluminum Oxide	1344-28-1	BD1200000
Alumino-Silicate, Hydrous	1332-58-7	GF1670500
Titanium Dioxide	13463-67-7	XR2275000
Iron Oxide (trace)	1309-37-1	NO7400000
Quartz, Crystalline Silica	14808-60-7	VV7330000

This product contains crystalline silica; once inhaled, cristobalite can remain in the lungs causing scarring, stiffening and difficulty breathing. The most common type of silicosis develops following repeated inhalation over time. Repeated inhalation of crystalline silica can also increase the risks of developing respiratory cancer. Although OSHA has not promulgated a specific standard for crystalline silica, materials that contain >= 0.1% crystalline silica should be treated as a confirmed carcinogen for hazard communication purposes.

## 12. ECOLOGICAL INFORMATION

Ecotoxity: Not tested Environmental Fate: Not tested

Physical/Chemical: Sinks and mixes with water. Only water will evaporate from this material.

### 13. DISPOSAL CONSIDERATIONS

Disposal Method: Dispose in accordance with federal, state and local regulations and permits.

## 14. TRANSPORTATION INFORMATION

**DOT UN Status:** The material is not a regulated hazardous material for transportation.

## 15. REGULATORY INFORMATION

#### **U.S. Federal Regulations**

CERCLA: No CERCLA reportable quantity has been established for this material.

TSCA: All ingredients of this material are listed on the TSCA inventory.

SARA Title III

Sections 302, 304, 313: This product does not contain any substances reportable under these sections.

Sections 311, 312:

Hazard Classes	Yes/No
Fire Hazard	No
Reactivity Hazard	No
Pressure Hazard	No
Immediate Hazard	Yes
Delayed Hazard	No
International Inventory	<u>Status</u>
Canada (DSL)	Yes
Europe (EINECS/ELINCS)	Yes
A 1 1: (A100)	
Australia (AICS)	Yes

## **16. OTHER INFORMATION**

NFPA: Health: 1

Flammability: 0 Reactivity: 0

#### **Key Legend Information**

South Korea (KECL)

ACGIH American Conference of Governmental Industrial Hygienists

ARD International Agency for Research on Cancer

Yes

CAS Chemical Abstract Service

CERCLA Comprehensive Environmental Response, Compensation & Liability Act

**DSL** Domestic Substance List

HMIS Hazardous Materials Identification System

ND Not Determined NE Not Established

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety & Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration
PEL Permissable Exposure Limit
RTECS Registry of Toxic Effects of Chemical Substances
SARA Superfund Amendments & Reauthorization Act

SARA Superfund Amendments & Reauthorization Act
SARA Title III Emergency Planning & Community Right to Know Act

SARA Section 302 Extremely Hazardous Substances

SARA Section 304 Emergency Release

SARA Section 311 MSDS/List of Chemicals & Hazardous Inventory

SARA Section 312 Emergency & Hazardous Inventory
SARA Section 313 Toxic Chemicals & Release Reporting

STELShort Term Exposure LimitTLVThreshold Limit ValueTWATime Weighted Average

**Disclaimer:** The information contained herein is based on data taken from sources believed to be both current and reliable at the time of publication. Aremco Products, Inc. makes no warranty, expressed or implied, as to the accuracy of this MSDS and assumes no liability arising from its use by others. Compliance with all applicable Federal, State and Local laws and regulations remains the responsibility of the user.